

## Jensolin White Cement Based Putty

Jensolin White Cement Based Putty is made from specially formulated powder polymers and functional additives that help in filling and leveling existing wall imperfections. This lends excellent aesthetic appearance to the top coat.

### PRODUCT BENEFITS



- Ideal Base for Concrete/ Plastered Surfaces
- Water Resistant
- Smooth & Hard Finish
- Quick & Easy Repair
- Strong & Adhesive Bonding
- High Durability



### PRODUCT FEATURES

#### AVAILABLE PACK SIZES



20 Kg



40 Kg

#### COVERAGE



12-15\* sq. ft. / Kg for two coats (by putty knife) finish under normal conditions

\*Actual coverage may vary due to factors such as method and condition of application, surface roughness and porosity and weather conditions.

#### RECOMMENDED USE

Jensolin White Cement Based Putty can be used on interior and exterior smooth plasters, false ceilings, asbestos sheets, concrete, etc.



#### SURFACE DRYING TIME



#### Technical Data:

Colour	:	White
Recommended Dilution	:	400 - 500 ml / Kg with clean potable water
Surface Dry time	:	25 minutes* (25°C / 50% RH)
Over coating period	:	6 - 8 hrs* (25°C / 50% RH)
Recommended DFT	:	Limit the total thickness of two coats to 1.5 mm

\*Recoat and drying period may vary under different conditions



WOOD COATINGS

# INTERMEDIATE COAT

## HOW TO PREPARE (SURFACE / WALL)

### Cleaning:

- Ensure that the surface is free from dust, dirt, chalking, oil, grease, loosely bound particles or any other contamination.
- Ensure removal of Algae and Fungal growth, if any using wire brushing and bio wash solution.
- Sand the glossy surface using Emery Paper 180, as it results in a roughened surface for good adhesion of the primer to the surface.
- Apply one coat of Jenson & Nicholson Water Thinnable Interior / Exterior Cement Primer at the recommended dilution level, using standard brush application. Let it dry for minimum 3-4 hours. Using Emery Paper 180, sand the surface lightly. Wipe clean.



**New concrete, masonry or plaster:** Allow the newly constructed cement surface to cure for minimum of 30 days, prior to application of Jenson & Nicholson Acrylic Base Water Thinnable Interior / Exterior Cement Primer. Ensure that the wall to be painted is completely dry and free from any cement residue.

### HOW TO APPLY ?

- Wet the applied primer, before application of Putty.
- Apply one coat of Jenson White Cement Based Putty using Putty Knife. Smooth the surface by filling dents, holes and imperfections. Allow it to dry for 6-8 hrs.
- Apply a second layer of putty, if required. Allow Putty to dry thoroughly, preferably overnight.
- Sand the surface with fine Emery Paper and wipe clean to get a leveled surface.
- Apply topcoat on the finished surface, after application of another coat of primer.

### Application precautions:

- Use only when the ambient temperature is between 10°C and 45°C.
- Do not dilute the product above the suggested dilution levels.
- This wall putty is not recommended for filling structural cracks.
- Seal the container, when not in use.

### Pot Life of Prepared Paste:

It is recommended to use the prepared paste within one hour, once it is mixed.

### For product related queries, feedback and quality complaints, Please contact:

Customer care: +91 8300 03 05 05

E-mail: [ccc@jnpl.in](mailto:ccc@jnpl.in),

Visit us: [www.jnpl.in](http://www.jnpl.in)

Regd. Office: Jenson & Nicholson Paints Private Ltd.

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600 098. Tamil Nadu, INDIA.

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.

Ver:2.0 / TDS / 2020



WOOD COATINGS

### Storage and Transportation:

- Do not store or transport the putty pack under moist conditions
- Keep away from any source of water.

### Shelf Life:

One year from the date of manufacture in the original sealed bags, stored away from direct sunlight and excessive heat.

### Pack Size:

Available in 20 kg and 40 kg packs.

### WHAT ARE THE PRECAUTIONS ?

- Keep containers upright, tightly closed in a cool, dry, well ventilated place.
- Ensure opened containers are tightly closed, when not in use.
- Store away from excessive heat, direct sunlight and other flammable materials.
- Highly Flammable product so, store in place away from heat and sparks and No smoking to be allowed near the product.
- Keep out of reach of children and pets.
- Do not store near food, drinks or animal feed.
- Do not mix with incompatible materials.
- Use personal protective equipment like goggles, face masks and gloves.
- Ensure good ventilation during application and drying.
- Do not inhale the vapour or spray.
- In case of contact with eyes or skin, wash immediately using plenty of water. Seek medical advice, if irritation persists.
- In case of ingestion, seek immediate medical attention and do not induce vomiting.
- Do not dispose any spilled or unused paint in drain, water bodies and landfill.
- Dispose spillages or unused paint and containers, through appropriate disposal agency.



**Jenson & Nicholson**

Whenever you see colour, think of us