

INTERMEDIATE COAT

Jenson & Nicholson Coarse Putty

Jenson & Nicholson Coarse Putty fills uneven surfaces in cement plastered walls, ceilings or concrete surfaces and is ideal for interior as well as exterior surfaces.

PRODUCT BENEFITS



- Water Resistant
- Rugged Finish
- Quick & Easy Repair
- Strong & Adhesive Bonding
- High Durability



PRODUCT FEATURES

AVAILABLE PACK SIZES



30 Kg

COVERAGE



12-15* sq. ft. / Kg for two coats (by putty knife)
finish under normal conditions

*Actual coverage may vary due to factors such as method and condition of application, surface roughness and porosity and weather conditions.

RECOMMENDED USE

Jenson & Nicholson Coarse Putty is recommended for all types of interior and exterior smooth plasters, false ceilings, asbestos sheets, concrete, etc.



SURFACE DRYING TIME



Technical Data:

Colour	:	White
Recommended Dilution	:	400 - 500 ml / Kg with clean potable water
Surface Dry time	:	25 minutes* (25°C / 50% RH)
Over coating period	:	6 - 8 hrs* (25°C / 50% RH)
Recommended DFT	:	Limit the total thickness of two coats to 1.5 mm

*Recoat and drying period may vary under different conditions



INTERMEDIATE COAT

HOW TO PREPARE (SURFACE / WALL)

Cleaning:

- Ensure that the surface is free from efflorescence and is clean and dry.
- Sand the surface using Emery Paper 180/ Wire brush to remove loosely bound particles, dust, dirt, grease, chalking, etc. Clean it with water. Wipe the surface clean.
- Apply one coat of J&N Water Thinnable Interior/ Exterior Cement Primer at the recommended dilution level, using standard brush application. Let it dry for minimum 3-4 hours. Using Emery Paper 180, sand the surface lightly. Wipe clean.



New concrete, masonry or plaster: Allow the newly constructed cement surface to cure for minimum of 30 days, prior to application of J&N Water Thinnable Interior/ Exterior Cement Primer. Ensure that the wall to be painted is completely dry and free from any cement residue.

HOW TO APPLY ?

- Apply one coat of J&N Coarse Putty using Putty Knife. Smooth and level the surface by filling dents, holes and imperfections. Allow it to dry for 6-8 hrs.
- Apply a second layer of putty, if required. Allow Putty to dry thoroughly, preferably overnight.
- For a smoother finish, apply one coat of Acrylic or Powder Putty.
- Sand the surface with fine Emery Paper and wipe clean.
- Apply topcoat on the finished surface, after application of another coat of primer.

Application precautions:

- Use only when the ambient temperature is between 10°C and 45°C.
- Do not dilute the product above the suggested dilution levels.
- This wall putty is not recommended for filling structural cracks.
- Seal the container, when not in use.

Pot Life of Prepared Paste:

It is advised to use the prepared paste within one hour, once it is mixed.

For product related queries, feedback and quality complaints, Please contact:

Customer care: +91 8300 03 04 04

E-mail: ccc@sheenlac.in,

Visit us: www.jnpl.in

Regd. Office: Jenson & Nicholson Paints Private Ltd.

(A joint venture of Jenson & Nicholson India Ltd and Sheenlac Paints Ltd)

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600 098. Tamil Nadu, INDIA.

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.

TDS / 2022 / Ver.1.0



WOOD COATINGS

Storage and Transportation:

- Store in the sealed bag away from direct heat/ sunlight.

Shelf Life:

One year from the date of manufacture in the original sealed bags, stored away from direct sunlight and excessive heat.

Pack Size:

Available in 30 kg packs.

PRECAUTIONS

- Keep containers upright, tightly closed in a cool, dry, well ventilated place.
- Ensure opened containers are tightly closed, when not in use.
- Store away from excessive heat, direct sunlight and other flammable materials.
- Flammable product, store in a place away from direct sunlight, heat and sparks.
- Keep out of reach of children and pets.
- Do not store near food, drinks or animal feed.
- Do not mix with incompatible materials.
- Use personal protective equipment like goggles, face masks and gloves.
- Ensure good ventilation during application and drying.
- Do not inhale the vapour or spray.
- In case of contact with eyes or skin, wash immediately using plenty of water. Seek medical advice, if irritation persists.
- In case of ingestion, seek immediate medical attention.
- Do not dispose any spilled or unused paint in drain, water bodies and landfill.
- Dispose spillages or unused paint and containers, through appropriate disposal agency.
- This product does not have any added Lead, Cadmium, Mercury & Chromium.